



For Dimension refer diagram A & B on page no. 19

Dimension : 96x96 | Panel Cutout : 92x92

Description	1Ø VOLTMETER	1Ø AMPERE METER	1Ø POWER METER
<b>Model</b>	<b>VIPS91</b> (96x96), <b>VIPS91P</b> (96x48)	<b>VIPS92</b> (96x96), <b>VIPS92P</b> (96x48)	<b>VIPS999</b> (96x96), <b>VIPS999P</b> (96x48)
<b>Display</b>	7 segment LED display, 0.56"		
<b>Digits</b>	4 digit 1 row		
<b>Input Volts</b>	0-500VAC (L-L), 0-300VAC (L-N)	—	0-300VAC (L-N)
<b>Input Ampere</b>		0.015 - 6.00A / Direct 60 ampere optional	
<b>Resolution</b>	Auto ranging, Hz 0.01	Auto ranging	Energy 0.1 kWh, PF 0.001, Hz 0.01 Auto ranging for volts / ampere & Power
<b>CT Primary</b>	—	Programmable up to 10000A	
<b>CT Secondary</b>	—	1A / 5A Programmable	
<b>PT Ratio</b>	Up to 132 kV	—	Up to 132 kV
<b>Communication</b>	RS485 Modbus (On special request)		
<b>Burden</b>	3VA Max. for Auxiliary supply, 0.2VA for Voltage & Current input		
<b>Update Time</b>	1 Sec		
<b>Scroll</b>	Auto / Manual		
<b>Parameter</b>	Volts, Hz, THD V	Amps, THD I	Volts, Amps, Hz, PF, Active Power, Reactive Power, Apparent Power, Energy, THDV, THDI, Load hours
<b>Temperature / Humidity</b>	Operating: -10°C to 55°C, Storage: -20°C to 75°C < 95% RH		