



For Dimension refer diagram A & B on page no. 19

Dimension : 96x96 | Panel Cutout : 92x92

Description	1Ø VOLTMETER	1Ø AMPERE METER	1Ø POWER METER
Model	VIPS91 (96x96), VIPS91P (96x48)	VIPS92 (96x96), VIPS92P (96x48)	VIPS999 (96x96), VIPS999P (96x48)
Display	7 segment LED display, 0.56"		
Digits	4 digit 1 row		
Input Volts	0-500VAC (L-L), 0-300VAC (L-N)	—	0-300VAC (L-N)
Input Ampere	—	0.015 - 6.00A / Direct 60 ampere optional	
Resolution	Auto ranging, Hz 0.01	Auto ranging	Energy 0.1 kWh, PF 0.001, Hz 0.01 Auto ranging for volts / ampere & Power
CT Primary	—	Programmable up to 10000A	
CT Secondary	—	1A / 5A Programmable	
PT Ratio	Up to 132 kV	—	Up to 132 kV
Communication	RS485 Modbus (On special request)		
Burden	3VA Max. for Auxiliary supply, 0.2VA for Voltage & Current input		
Update Time	1 Sec		
Scroll	Auto / Manual		
Parameter	Volts, Hz, THD V	Amps, THD I	Volts, Amps, Hz, PF, Active Power, Reactive Power, Apparent Power, Energy, THDV, THDI, Load hours
Temperature / Humidity	Operating: -10°C to 55°C, Storage: -20°C to 75°C < 95% RH		